




**TopCon
Bifacial
C•BLACK^{tech}**

30-year linear power
output warranty
15-years product warranty

**HELIUS
GENESIS**

HMB132T10R
570W - 590W

PREMIUM N-TYPE CELLS
MBB HALF CELL TECHNOLOGY




INMETRO, IEC 61215, IEC 61730, IEC TS 62804, IEC 61701
ISO 9001:2008 - ISO 14001:2004 - OSHAS 18001:2007



SUPERIOR QUALITY

With MBB technology and half cell design, Helius Energy panels reduce cover of cell by busbars and improve current collection ability on cloudy days.



HIGH EFFICIENCY AND POWER DENSITY

High conversion efficiency and up to 590W. More gain power per square meter.



PERFORMANCE WARRANTY

With up to 30 years of solar generation, Helius Energy warranty can guarantee the longevity of your project.




FIRE-PROOF PERFORMANCE

Modules are approved and tested under IEC 61730 and Class C Fire Test.



LIGHT AND RELIABLE

Much lighter modules with thicker frames to ensure module resilience. Modules could be applied under ammonia, salt mist, high temperature, high humidity condition.




MECHANICAL CHARACTERISTICS

Dimensions	2278 x 1134 x 30mm
Solar Cells	132 Monocrystalline N-Type Cells
Weight	31.2 kg
Frame	Black Composite
Glass	Double 2.0 mm High Transmission, Low Iron Tempered
J-Box	IP68 / 3 bypass diodes
Cables	4mm / Length 1200mm or customized

TEMPERATURE CHARACTERISTICS


Temperature Coefficient Isc	0.046% / °C
Temperature Coefficient Voc	-0.26% / °C
Temperature Coefficient Pmax	-0.30% / °C
Nominal Module Operating Temperature NMOT	44°C + -2°C
Operational Temperature	-40°C a +85°C



ELECTRICAL CHARACTERISTICS

HMB132T10R	570CB	575CB	580CB	585CB	590CB
Maximum Power PMax (W)	570	575	580	585	590
Maximum Power Voltage Vmp (V)	40.03	40.21	40.42	40.64	40.82
Maximum Power Current Imp (A)	14.24	14.30	14.35	14.41	14.47
Open Circuit Voltage Voc (V)	47.77	47.98	48.18	48.39	48.60
Short Circuit Current Isc (A)	15.10	15.16	15.21	15.25	15.29
Module Efficiency	22.1%	22.3%	22.5%	22.7%	22.9%
Maximum System Voltage	1500VCC				
Maximum Series Fuse	30A				

Test Conditions: 1000W/m², 25°C, AM=1.5



ELECTRICAL CHARACTERISTICS WITH REAR POWER GAIN (580W)

Pmax Gain (%)	10%	20%	30%
Maximum Power PMax (W)	609	696	754
Maximum Power Voltage Vmp (V)	40.42	40.42	40.42
Maximum Power Current Imp (A)	15.79	17.22	18.65

PACKAGING CONFIGURATION

Modules per Container 40HQ	720 pcs
Pallets per Container 40HQ	20
Modules per Pallet	36
Pallet Dimensions	2307 x 1207 x 1196mm
Gross Weight per Pallet (kg)	1155

Helius Energy reserves the right to change data and specifications without notices. All rights are reserved to Helius Energy. For more Informations, contact a technical representative or www.he-solar.com

DECEMBER 2024

