



HELIUS GENESIS


HMF144T10R
580W - 600W

PREMIUM N-TYPE MONOCRYSTALLINE CELLS
MBB HALF CELL TECHNOLOGY

30-year linear power output warranty

15-years product warranty

SUPERIOR WARRANTY



INMETRO, IEC 61215, IEC 61730, IEC TS 62804, IEC 61701
ISO 9001:2008 - ISO 14001:2004 - OSHAS 18001:2007

SUPERIOR QUALITY

With MBB technology and half cell design, Helius Energy panels reduce cover of cell by busbars and improve current collection ability on cloudy days.

HIGH EFFICIENCY AND POWER DENSITY

High conversion efficiency and up to 600W. More gain power per square meter.

PERFORMANCE WARRANTY

With up to 30 years of solar generation, Helius Energy warranty can guarantee the longevity of your project.


FIRE-PROOF PERFORMANCE

Modules are approved and tested under IEC 61730 and Class C Fire Test.

LIGHT AND RELIABLE

Much lighter modules with thicker frames to ensure module resilience. Modules could be applied under ammonia, salt mist, high temperature, high humidity condition.

RECOGNIZED FOR **Tier 1**




MECHANICAL CHARACTERISTICS

Dimensions	2333 x 1134 x 30mm
Solar Cells	144 Monocrystalline N-Type Cells
Weight	27.2 kg
Frame	Anodized Aluminium Alloy
Frontal Glass	3.2 mm High Transmission, Low Iron Tempered
J-Box	IP68 / 3 bypass diodes
Cables	4mm / Length 1200mm or Customized

TEMPERATURE CHARACTERISTICS


Temperature Coefficient I _{sc}	0.045% / °C
Temperature Coefficient V _{oc}	-0.25% / °C
Temperature Coefficient P _{max}	-0.30% / °C
Nominal Module Operating Temperature NMOT	44°C ±2°C
Operational Temperature	-40°C ~+85°C



ELECTRICAL CHARACTERISTICS

HMF144T10R	580HL	585HL	590HL	595HL	600HL
Maximum Power P _{Max} (W)	580	585	590	595	600
Maximum Power Voltage V _{mp} (V)	43.06	43.22	43.42	43.62	43.82
Maximum Power Current I _{mp} (A)	13.47	13.53	13.59	13.62	13.70
Open Circuit Voltage V _{oc} (V)	51.60	51.8	52.00	52.12	52.29
Short Circuit Current I _{sc} (A)	14.23	14.32	14.35	14.40	14.44
Module Efficiency	22.1%	22.2%	22.3%	22.4%	22.5%
Maximum System Voltage	1500VCC				
Maximum Series Fuse	25A				

Test Conditions: 1000W/m², 25°C, AM =1.5



PACKAGING CONFIGURATION

Modules per Container 40HQ	720 pcs
Pallets per Container 40HQ	20
Modules per Pallet	36
Pallet Dimensions	2376 x 1260 x 1196mm
Gross Weight per Pallet (kg)	1020

Helius Energy reserves the right to change data and specifications without notices. All rights are reserved to Helius Energy. For more Informations, contact a technical representative or www.he-solar.com

DECEMBER 2024

